



HYDROXPLAST WATERBORNE FOR EXTERIOR PLASTICS



1K PRODUCT FOR
EXTERIOR PLASTICS

HIGH OUTDOOR
DURABILITY

APPLICATION
VERSATILITY

AJ1330/NN

HYDROXPLAST WATERBORNE FOR EXTERIOR PLASTICS AJ1330/NN

AJ1330/NN converter is a neutral waterborne topcoat 30 gloss for outdoor use and it's the ideal solution for plastic substrate such as PVC.

It can be tinted with the standard Sayerlack waterborne pastes of series XA2006/XX.

Prior to application it is necessary to remove the grease from the substrate using the specific thinner **DT1150/00**, **DT0015/00** or **DT0013/00**.

AJ1330/NN exhibits good thixotropy and can be applied even vertically in thick coats (max. 225 g/m² wet) with no sagging. Addition of pigment pastes may reduce hold up, requiring application of lower film weights.

TECHNICAL CHARACTERISTICS		
APPLICATION	Spray (conventional, airmix, airless and electrostatic)	
DRYING TIME (120 g/m ² at 20°C)	Dust free	40'
	Touch free	2 h
	Sanding	6 h
	Stacking	24 h
FORCED AIR DRYING (120 g/m ²)	Flash off	20'
	Hot air at 40°C	120'
	Cooling	20'
AREA OF USE	PVC window frames and wooden parts exposed outdoor	

Technical Service: Ph. +39 051 770770 - Fax +39 051 770521 customerservice@sayerlack.com

Sherwin-Williams Italy S.r.l. - Export Department
Via del Fiffo 12 - 40065 Pianoro (BO) - Italy
Ph. +39 051 770511 - Fax +39 051 770528
export@sayerlack.it - www.sayerlack.com



Sayerlack is a brand of The Sherwin Williams Company