



WATER-BASED AND SOLVENT-BASED COATINGS SYSTEMS LIGHT FAST EFFECT



GREATER STABILITY TO LIGHT ON RECONSTITUTED VENEER

EXCELLENT PERFORMANCE ON VENEERS

EXCELLENT PORE DESIGN ON NATURAL EFFECT FINISHES

REDUCED QUANTITY OF ADDITIVES USED

UV ABSORBERS





WATER-BASED AND SOLVENT-BASED COATINGS SYSTEMS LIGHT FAST EFFECT

In order to satisfy the growing demand from architects and designers for products capable of ensuring the light consolidation of nautical furniture and furnishings, Sayerlack offers innovative and high-performance water-based and solvent-based solutions, thanks to the use of new topcoats and additives. These new high-performance Sayerlack systems achieve superior results in terms of light stability on numerous types of wood, ensuring excellent levels of protection and stability on multi-laminars, reconstituted Veneer and veneers.

WATER-BASED COATING SYSTEM FOR PROTECTION FROM LIGHT

The innovation consists in inserting a consolidant within a high-performance standard system, to be applied directly on the chosen substrate as if it were a tint, first coat. The other key element is a specific UV barrier additive which must be added to the product chosen for the finish, this preferably two-component to optimize the consolidation of the barrier in the paint film, to complete its system. This solution ensures greater stability to light over time and the possibility of obtaining open-pore or natural-effect systems. Furthermore, the synergy between these new elements makes it possible to obtain the same performance even with the application of reduced thicknesses of the applied product.

WB system example

1) Consolidant (XAV5951/00)

30-40 g of consolidant as if it were a dye, to be left to dry

2) Basecoat/Non-yellowing self-sealer

Apply a non-yellowing two-pack with 3% UV barrier additive (XAL5956/00) and sand.

3) Self-sealer / Non-yellowing topcoat

Add 3% UV barrier additive (XAL5956/00), apply and leave to dry for 12-16 hours

SOLVENT COATING SYSTEM FOR PROTECTION FROM LIGHT

Sayerlack has developed a new clear acrylic-based self-sealer (5 and 10 gloss) which can be applied both with conventional manual or automatic spraying methods, and with a curtain coater, capable of allowing the achievement of significantly higher than average performance in terms of protection from light, and presenting excellent pore definition, slip and chemical-physical performance. The excellent results of these systems in terms of light stability are ensured by the addition of a limited quantity (1%) of UV barrier additive in the basecoat and topcoat used.

SB system example

1) first coat of self-sealer (TU75XX/00)

Add 1% of UV barrier additive (XTL3465/00) to the product, catalyze and apply 100-120 g/m²

2) Drying

Leave to dry for at least 2 hours then sand with fine grain

3) Second coat of self-sealer (TU75XX/00)

Add 1% of UV barrier additive (XTL3465/00) to the product, catalyze and apply 120-130 g/m²

Technical Service: Ph. +39 051 770770 - Fax +39 051 770521 customerservice@sayerlack.com

Sherwin-Williams Italy S.r.l. - Export Department

Via del Fiffo 12 - 40065 Pianoro (BO) - Italy

Ph. +39 051 770511 - Fax +39 051 770528

export@sayerlack.it - www.sayerlack.com



Sayerlack is a brand of The Sherwin Williams Company