



SATIN GUARD HP 2K POLYURETHANE TOPCOAT

SMOOTH & SATIN TOUCH

ANTI-FINGERPRINT

ULTRA LOW GLOSS

SUPERB MECHANICAL &
CHEMICAL RESISTANCE

EFFORTLESSLY
REPAIRABLE &
CLEANABLE SURFACE

TZ0303/00 Clear
TZ0303/13 White





SATIN GUARD - POLYURETHANE SB TOPCOAT TZ0303/00 Clear - TZ0303/13 White

The innovative High Performances solvent-borne ultra matt finishing, designed for the furniture, furnishing accessories and kitchen sectors.

Satin Guard HP is the perfect choice for customers seeking high chemical performance, mechanical resistance, and excellent hiding power.

2k Special Polyurethane formulation with high chemical performances and physical resistances. The surface finish durability is guaranteed by its unique properties, allowing effortless cleaning and the removal of superficial scratches. With very good self-reparability performance, Satin Guard HP offers a long-lasting, high-quality finish that is both beautiful and functional.

Alternative to latest technologies as excimer and plastic-foils, with the advantage of not directional spray application, good for every surface, even tridimensional. Without any need of additional investments or machinery. It can be applied on any kind of solvent basecoat or directly on sanded melamine paper. Very good adhesion and hiding power in a single layer (120 g/m², spray).

Fully compatible with our tinting- system, ensuring unlimited colour matching and customization using limited quantity of standard solvent borne pastes (< 10%).

TECHNICAL FEATURES

PRODUCT	GLOSS	CODE	TYPE	COVERAGE	DRYING CONDITIONS	DRYING TIME
SATIN GUARD HP	2 +/- 1	TZ0303/00	Clear	100-150 g/m ²	100 g/m ² Room temperature 20°C	Touch dry 2-4h
						Through dry 24h
		TZ0303/13	White	120-170 g/m ²	120 g/m ² Room temperature 20°C	Touch dry 3-4h
						Through dry 36h

Please refer to official products TDS (Technical Data sheets) for additional information and application suggestions.

Substrate preparation.

The substrates can be prepared with PU primers of the desired colour, for TZ0303/00. Use standard PU/PE primers for TZ0303/13. The product can be pigmented with TP2009/XX pastes, at a percentage between 5-10% by weight.

Technical Service: Ph. +39 051 770770 - Fax +39 051 770521 customerservice@sayerlack.com

Sherwin-Williams Italy S.r.l.

Via del Fiffo 12 - 40065 Pianoro (BO) - Italia
Tel. +39 051 770511 - Fax +39 051 777437
info@sayerlack.it - www.sayerlack.it



Sayerlack is a brand of The Sherwin Williams Company